DOWNLIGHT



Cutout


FLOLITE by Man-D-Tec®

PATENTED, COMPACT FLUORESCENT LIGHTING FIXTURE, DESIGNED SPECIFICALLY FOR ELEVATOR APPLICATIONS.

Warm white 26 watt output per fixture. Fixtures include a pre-mounted handy box for easy installation. The fixture diameter and exclusive, easy-mount design is the same as our MegaBeam $^{\text{m}}$ series.

Product Specifications on the back of page.









Fixture

(FLOLITE)

MATERIAL (TRIM) One-piece aluminum

DIMENSIONS 4.00" 6.63"

Cutout Hole

Overall Height

8.00" Overall Diameter Uses Same Hole Cutout Size as Our MegaBeam™ Fixtures.

ELEVATOR CONTROL, ELEVATOR ACCESSORY

FINISHES

BULB

Black **Brushed** Powder Coat **STANDARD** #4 Silver Brushed Finish (Option)

Polished High Luster #8 Mirror Finish (Option) White Powder Coat (Option) Gold Powder Coat (Option)

SOCKET

2 pin snap-in

PL-S-13-C 13 watt w/ protective coating (2 required per fixture)

TO REPLACE LAMPS

In order to replace the compact fluorescent bulbs, grasp the reflector trim with both hands and start rotating the trim as you pull downward. Once the trim is removed, each of the bulbs can be removed from the base and replaced with our PL-S-13-C coated, 13 watt, 2 pin base bulb. Once the bulbs have been replaced, reinsert the trim by pushing straight up into the lamp housing.

Outer Housing **MATERIAL**

One-piece aluminum

MOUNTING

Integrated tabs (requires four (4) screws)



ELEVATOR CONTROL, ELEVATOR ACCESSORY

Wiring

VOLTAGE

Input: 115 VAC

Pigtail wires ready for wiring in pre-mounted, integrated handy box

Emergency (Optional)

ELS-500°

Powers (2) two Flolite fixtures during a normal power failure.

EXCEEDS A17.3 4-HOUR RUNTIME CODE REQUIREMENT FOR EMERGENCY LIGHTING.